

Eco Wash Neutral

Description

Eco Wash Neutral is a mild cleaner that easily removes dirt from buses, metros, trams, trains, cars, etcetera. This product can be used for both the outside and the inside. The product is also environmentally friendly and has the Nordic Swan Ecolabel.

Usage

Eco Wash Neutral can be applied to:

- Buses
- Trains
- Trams
- Metros
- Trucks
- etcetera.

Advantages

Advantages of the **Eco Wash Neutral** are:

- Eco-certified with the Nordic Swan Ecolabel
- Removes dirt easily
- Economical in use

Application Tools

Apply **Eco Wash Neutral** with a low-pressure sprayer or a mop:



Health and Safety

- Breathing Protection: No breathing protection is required under normal use conditions with suitable ventilation. Wearing a facemask is advisable.
- Hand protection: Chemical resistant gloves should be worn.
- Skin protection: Wear protective clothing over exposed areas of skin.
- Eye protection: Chemical goggles should be worn.
- Ingestion: Ingestion may cause nausea and vomiting. Do not induce vomiting. Consult a Doctor.

KEEP OUT OF THE REACH OF CHILDREN!

Recommendation

Always carry out a test first to ensure the finished result is acceptable.

Ideal processing temperature is 5 °C – 30 °C. The ideal processing temperature for the substrate is 5°C – 25°C.

Do not let the product dry in the sun.

Coverage rate

2 – 5m² / liter.

Depending on the degree of dirt.

Dilute

Car	1:10 – 1:50
Truck	1:10 – 1:25
Train	1:10 – 1:25
Special machines	1:4 – 1:10

Depending on the degree of dirt



Eco Wash Neutral

Application

The product is concentrated and must be diluted with water. Depending on the dirt and temperature. Apply the product with a low-pressure sprayer or a mop. Do not let the product dry on the surface. For best results on floors, use a mop.

Equipment care

All equipment should be cleaned with water after use.

Storage

Recommended storage is in a cool, dry place with temperature 5°C – 25°C.
Store frost free.

Shelf life: 12 months in original sealed container.

Technical Support

For technical support, please do not hesitate to contact us.

Protectcoat International
Spinding 16
5431 SN CUIJK
The Netherlands

Postbus 36
5430 AA CUIJK
The Netherlands

T: +31 (0)85-06 55 797

W: www.protectcoatint.com

Follow us on Social Media.



Important:

The content of this documentation is based on our experience with the product. Protectcoat International guarantees the quality of this products but expressly disclaims all liability if the user does not follow the recommendations and conditions of use of the products, especially but not exclusively in the case of faulty application, application by untrained personnel, use of products not compatible with Protectcoat International products or adverse weather conditions. For more information, consult the Safety Data Sheet. Protectcoat International accepts no liability arising from printing errors, mistakes/typing errors.

For the latest information, visit our website.
www.protectcoatint.com

Last updated: 01/07/2022

