

Protectcoat AG30 Coating

Description

Protectcoat AG30 Coating is a clear, permanent and a 1 compound anti-graffiti coating. The coating is suitable for painted metal, aluminum, plastic etc.

Protectcoat AG30 Coating is a high quality coating and has been approved by the Deutsche Bahn AG. The anti graffiti coating offers a long lasting protection of 8-10 years (tapering). Removing ink, graffiti, posters etc. is very easy. The coating has a good chemical, scratch and weather resistance.

Usage

Protectcoat AG30 Coating can be applied to painted surfaces such as:

- Metal
- Plastic
- Aluminium
- Etcetera.

Advantages

The advantages of **Protectcoat AG30 Coating** are:

- Permanent coating
- 1 compound
- UV resistant
- Protective coating with gloss
- Tested and meets the requirements of the Deutsche Bahn AG

Application Tools

Apply **Protectcoat AG30 Coating** with a clean microfiber cloth or a melamine sponge:



Health and Safety

- Breathing Protection: No breathing protection is required under normal use conditions with suitable ventilation. Wearing a facemask is advisable.
- Hand protection: Chemical resistant gloves should be worn.
- Skin protection: Wear protective clothing over exposed areas of skin.
- Eye protection: Chemical goggles should be worn.
- Ingestion: Ingestion may cause nausea and vomiting. Do not induce vomiting. Consult a Doctor.

KEEP OUT OF THE REACH OF CHILDREN!

Advice

Always carry out a test first to ensure the finished result is acceptable.

Air temperature between 5°C – 30°C.

Substrate temperature 5°C – 25°C

Attention:

It is very important that the surface is not damp or wet. The product is very sensitive to moisture. Film formation may occur due to humidity and low temperatures.

Coverage rate

125-150m² / liter.



Protectcoat AG30 Coating

Application

Preparation:

Attention: the product must not be exposed to frost. The surface must be dry, dust-free and clean.

Application:

Apply **Protectcoat Colour RC** with a clean microfiber cloth or a melamine sponge. Apply a thin layer of approximately 5 µm.

Drying time:

Dry:	approx. 20 minutes
Dry on surface:	approx. 120 minutes
Hardened:	approx. 12 hours

Based on +/- 20 °C.

Storage

Recommended storage is in a cool, dry place with temperature 10°C – 15°C.

Store the product in a frost-free place.

Shelf life: 12 months in original sealed container.

Technical support

For technical support, please do not hesitate to contact us.

Protectcoat International
Spinding 16
5431 SN CUIJK
The Netherlands

Postbus 36
5430 AA CUIJK
The Netherlands

T: +31 (0)85-06 55 797
W: www.protectcoatint.com

Follow us on Social Media.



Important:

The content of this documentation is based on our experience with the product. Protectcoat International guarantees the quality of this products but expressly disclaims all liability if the user does not follow the recommendations and conditions of use of the products, especially but not exclusively in the case of faulty application, application by untrained personnel, use of products not compatible with Protectcoat International products or adverse weather conditions. For more information, consult the Safety Data Sheet. Protectcoat International accepts no liability arising from printing errors, mistakes/typing errors.

For the latest information, visit our website.
www.protectcoatint.com

Last updated: 01/01/2022