

# Protectcoat AG50 Coating

## Description

**Protectcoat AG50 coating** is a clear, sacrificial and a semi-permanent anti-graffiti coating. Protectcoat AG50 coating is an environmentally friendly coating based on polysaccharide (potato starch). This anti-graffiti coating can be used on various absorbent surfaces such as: concrete, brick, granite, etc. To remove future graffiti, ink or glue, it requires only hot water under appropriate pressure. No chemical removers are needed. After removal, re-coating of the cleaned areas is required. The coating provides 3-5 years of protection, depending on the surface and environment.

## Usage

**Protectcoat AG50 coating** can be applied to:

- Concrete
- Brick
- Stone
- et cetera


## Advantage

Advantages of **Protectcoat AG50 coating** are:

- Clear coating
- Dirt-repellent
- Contains natural ingredients (potato starch)
- Vapour-permeable
- No chemical removers needed

## Application Tools

Apply **Protectcoat AG50 Coating** with a roller or a paint sprayer.



## Health and Safety

- Breathing Protection: No breathing protection is required under normal use conditions with suitable ventilation. Wearing a facemask is advisable.
- Hand protection: Chemical resistant gloves should be worn.
- Skin protection: Wear protective clothing over exposed areas of skin.
- Eye protection: Chemical goggles should be worn.
- Ingestion: Ingestion may cause nausea and vomiting. Do not induce vomiting. Consult a Doctor.

KEEP OUT OF THE REACH OF CHILDREN!

## Recommendation

Always carry out a test first to ensure the finished result is acceptable.

Ideal processing temperature is 5 °C – 30 °C.

The ideal processing temperature for the substrate is 5°C – 25°C.

Do not let the product dry in the sun.

## Coverage rate

0,5 – 6m<sup>2</sup> / liter.

Depending on the surface.

# Protectcoat AG50 Coating

## Application

**Preparation:** The surface must be dry, dust-free and clean. Shake the product well before use.

### Application:

Apply **Protectcoat AG50 coating** with a roller. For full coverage, it is recommended to apply the product crosswise. Make sure the entire surface is covered.

### Drying time:

120 min. – 180 min. depending on the temperature, layer thickness and the environment.

## Equipment care

All equipment should be cleaned with water after use.

## Storage

Recommended storage is in a cool, dry place with temperature 5°C – 25°C.  
Store frost free.

Shelf life: 12 months in original sealed container.

## Technical Support

For technical support, please do not hesitate to contact us.

**Protectcoat International**  
**Spinding 16**  
**5431 SN CUIJK**  
**The Netherlands**

**Postbus 36**  
**5430 AA CUIJK**  
**The Netherlands**

**T:** +31 (0)85-06 55 797

**W:** [www.protectcoatint.com](http://www.protectcoatint.com)

**Follow us on Social Media.**



### Important:

The content of this documentation is based on our experience with the product. Protectcoat International guarantees the quality of this products but expressly disclaims all liability if the user does not follow the recommendations and conditions of use of the products, especially but not exclusively in the case of faulty application, application by untrained personnel, use of products not compatible with Protectcoat International products or adverse weather conditions. For more information, consult the Safety Data Sheet. Protectcoat International accepts no liability arising from printing errors, mistakes/typing errors.

For the latest information, visit our website.  
[www.protectcoatint.com](http://www.protectcoatint.com)

Last updated: 01/01/2023