

# Protectcoat AG60 Coating

## Description

**Protectcoat AG60 Coating** is a clear and semi-permanent anti graffiti coating. Protectcoat AG60 Coating is an eco-friendly polysaccharide-based coating. This anti graffiti coating can be used on most types of hard non-absorbent surfaces such as steel containers, glass, plastic etc. To remove future graffiti only use warm water, no chemical removers. In case of using a pressure washer, there is new coating needed. Lifetime is 3-5 years, depending on the surface and environment.

## Usage

**Protectcoat AG60 Coating** can be used on:

- Glass
- Plastic
- Hard non-absorbent surface
- Etcetera.


## Advantage

The advantages of the **Protectcoat AG60 Coating** are:

- Eco friendly anti graffiti coating
- Clear coating
- Lifetime 3-5 years
- Permeable
- Remove graffiti easily without chemical removers

## Application Tools

Apply **Protectcoat AG60 Coating** with a roller or a paint sprayer.



## Health and Safety

- Breathing Protection: No breathing protection is required under normal use conditions with suitable ventilation. Wearing a facemask is advisable.
- Hand protection: Chemical resistant gloves should be worn.
- Skin protection: Wear protective clothing over exposed areas of skin.
- Eye protection: Chemical goggles should be worn.
- Ingestion: Ingestion may cause nausea and vomiting. Do not induce vomiting. Consult a Doctor.

KEEP OUT OF THE REACH OF CHILDREN!

## Recommendation

Always carry out a test first to ensure the finished result is acceptable.

Air temperature between 5°C – 30°C.

Substrate temperature 5°C – 25°C

## Coverage rate

0,5 m<sup>2</sup> / liter.



# Protectcoat AG60 Coating

## Application

### Preparation:

The surface must be dry, dust-free and clean. Shake the product before use. When applying the coating to newly painted surface, allow paint to dry for approx. 1-4 weeks before the applications takes place.

### Application:

Apply the **Protectcoat AG60 Coating** with a roller or a paint sprayer. Make sure the entire surface is covered. The anti graffiti coating should be applied in 2 layers.

### Dry time:

First layer 30 min. – 60 min.

Second layer 120 min. – 180 min.

Depending on the temperature, layer thicknesses and environment.

## Equipment care

All equipment should be cleaned with water after use.

## Storage

Recommended storage is in a cool, dry place with a temperature between 5°C – 30°C.

Shelf life: 12 months in original sealed container.

## Technical Support

For technical support, do not hesitate to contact us:

**Protectcoat International**  
**Spinding 16**  
**5431 SN CUIJK**  
**The Netherlands**

**Postbus 36**  
**5430 AA CUIJK**  
**The Netherlands**

**T:** +31 (0)85-06 55 797

**W:** [www.protectcoatint.com](http://www.protectcoatint.com)

## Follow us on Social Media.



### Important:

The content of this documentation is based on our experience with the product. Protectcoat International guarantees the quality of this products but expressly disclaims all liability if the user does not follow the recommendations and conditions of use of the products, especially but not exclusively in the case of faulty application, application by untrained personnel, use of products not compatible with Protectcoat International products or adverse weather conditions. For more information, consult the Safety Data Sheet. Protectcoat International accepts no liability arising from printing errors, mistakes/typing errors.

For the latest information, visit our website.

[www.protectcoatint.com](http://www.protectcoatint.com)

Latest update: 01/01/2022