

Protectcoat AGR3

Description

Protectcoat AGR3 is a graffiti remover that removes graffiti on sensitive substrates such as plexiglass, laminate, signboards, etc..

Usage

Protectcoat AGR3 can be applied to:

- Plexiglass
- Laminate
- Signboards
- Interior walls
- Etcetera.

Advantages

Advantages of **Protectcoat AGR3** are:

- Removes graffiti easily
- Perfect for sensitive surfaces
- Quick result

Application Tools

Apply the **Protectcoat AGR3** with a cloth:



Health and Safety

- Breathing Protection: No breathing protection is required under normal use conditions with suitable ventilation. Wearing a facemask is advisable.
- Hand protection: Chemical resistant gloves should be worn.
- Skin protection: Wear protective clothing over exposed areas of skin.
- Eye protection: Chemical goggles should be worn.
- Ingestion: Ingestion may cause nausea and vomiting. Do not induce vomiting. Consult a Doctor.

KEEP OUT OF THE REACH OF CHILDREN!

Recommendation

Always carry out a test first to ensure the finished result is acceptable.

Ideal processing temperature is 5 °C – 30 °C.
The ideal processing temperature for the substrate is 5°C – 25°C.

Do not let the product dry in the sun.

Coverage rate

0,2 – 0,5m² / liter.

Depending on the degree of dirt.



Protectcoat AGR3

Application

Apply the **Protectcoat AGR3** with a cloth. Immediately wipe away the graffiti by making small circular movements. Rinse the surface with clean water. In case multiple layer thicknesses or old graffiti residues, let the product soak for 2 - 3 minutes.

Equipment care

All equipment should be cleaned with water after use.

Storage

Recommended storage is in a cool, dry place with temperature 5°C – 25°C. Store frost free.

Shelf life: 12 months in original sealed container.

Technical Support

For technical support, please do not hesitate to contact us.

Protectcoat International
Spinding 16
5431 SN CUIJK
The Netherlands

Postbus 36
5430 AA CUIJK
The Netherlands

T: +31 (0)85-06 55 797

W: www.protectcoatint.com

Follow us on Social Media.



Important:

The content of this documentation is based on our experience with the product. Protectcoat International guarantees the quality of this products but expressly disclaims all liability if the user does not follow the recommendations and conditions of use of the products, especially but not exclusively in the case of faulty application, application by untrained personnel, use of products not compatible with Protectcoat International products or adverse weather conditions. For more information, consult the Safety Data Sheet. Protectcoat International accepts no liability arising from printing errors, mistakes/typing errors.

For the latest information, visit our website.
www.protectcoatint.com

Last updated: 01/07/2022