

# Protectcoat Concrete Remover

## Description

**Protectcoat Concrete Remover** is a cleaner to remove concrete (residue) from concrete skips, concrete mixer, metal formworks etcetera. Protectcoat Concrete Remover is a biodegradable product and user friendly. Protectcoat Concrete Remover will not damage the surface.

## Usage

Protectcoat Concrete Remover:

- Concrete skips
  - Concrete mixer (Trucks)
  - RMC Plants
  - Metal formworks
  - Concrete from clothes
- Etcetera.

## Advantages

The advantages of **Protectcoat Concrete Remover** are:

- User-friendly
- Biodegradable
- Non-Corrosive
- Safe on surface (safe on virtually every surface including aluminium, chrome, glass, rubber and plastic)
- It keeps vehicles and equipment looking new.

## Application Tools

Apply **Protectcoat Concrete Remover** with a low-pressure sprayer:



## Health and Safety

- Breathing Protection: No breathing protection is required under normal use conditions with suitable ventilation. Wearing a facemask is advisable.
- Hand protection: Chemical resistant gloves should be worn.
- Skin protection: Wear protective clothing over exposed areas of skin.
- Eye protection: Chemical goggles should be worn.
- Ingestion: Ingestion may cause nausea and vomiting. Do not induce vomiting. Consult a Doctor.

KEEP OUT OF THE REACH OF CHILDREN!

## Advice

Always carry out a test first to ensure the finished result is acceptable.

Air temperature between 5°C – 30°C.  
Substrate temperature 5°C – 25°C

Attention:

Avoid applying during heavy rain or very hot weather.

## Coverage rate

8-10 m<sup>2</sup> / Litre.

Depending on thickness of residue.



# Protectcoat Concrete Remover

## Application

Apply **Protectcoat Concrete Remover** with a sprayer on dry concrete and wait for 15 minutes or until concrete has turned to paste. If a paste has not formed, re-apply. This may occur with heavy buildup or older concrete. Allow to dwell 15 – 60 minutes before rinsing. (Depending on thickness of residue). Rinse with pressure washer.

## Equipment Care

Equipment Care All equipment should be cleaned with water after use

## Storage

Recommended storage is in a cool, dry place with temperature 10°C – 15°C.

Shelf life: 12 months in original sealed container.

## Technical support

For technical support, please do not hesitate to contact us.

**Protectcoat International**  
**Spinding 16**  
**5431 SN CUIJK**  
**The Netherlands**

**Postbus 36**  
**5430 AA CUIJK**  
**The Netherlands**

**T:** +31 (0)85-06 55 797  
**W:** [www.protectcoatint.com](http://www.protectcoatint.com)

**Follow us on Social Media.**



## Important:

The content of this documentation is based on our experience with the product. Protectcoat International guarantees the quality of this products but expressly disclaims all liability if the user does not follow the recommendations and conditions of use of the products, especially but not exclusively in the case of faulty application, application by untrained personnel, use of products not compatible with Protectcoat International products or adverse weather conditions. For more information, consult the Safety Data Sheet. Protectcoat International accepts no liability arising from printing errors, mistakes/typing errors.

For the latest information, visit our website.  
[www.protectcoatint.com](http://www.protectcoatint.com)

Last updated: 01/01/2022