

Protectcoat Ink-RT15

Description

Protectcoat Ink-RT15 is an ink remover. This ink remover comes in gel form. The ink remover is suitable for removing ink, marker and graffiti from the inside of trains, metros, trams and buses.

Usage

Protectcoat Ink-RT15 can be applied on the insides of:

- Trains
- Metros
- Trams
- Buses

Advantage

The advantages of **Protectcoat Ink-RT15** are:

- Removes ink, marker and graffiti easily
- Removes shadows
- Quick result
- Saves time with cleaning
- Can be used on various surfaces

Application Tools

Apply the **Protectcoat Ink-RT15** with a cloth:



Health and Safety

- Breathing Protection: No breathing protection is required under normal use conditions with suitable ventilation. Wearing a facemask is advisable.
- Hand protection: Chemical resistant gloves should be worn.
- Skin protection: Wear protective clothing over exposed areas of skin.
- Eye protection: Chemical goggles should be worn.
- Ingestion: Ingestion may cause nausea and vomiting. Do not induce vomiting. Consult a Doctor.

KEEP OUT OF THE REACH OF CHILDREN!

Recommendation

Always carry out a test first to ensure the finished result is acceptable.

Air temperature between 5°C – 30°C.

Substrate temperature 5°C – 25°C

Do not allow the product to dry in the sun.

Coverage rate

0,2 – 0,3m² / liter.

Depending on the degree of dirt.



Protectcoat Ink-RT15

Application

Apply **Protectcoat Ink-RT15** with a cloth. Make small circular movements on the to be treated surface. For stubborn ink or graffiti, allow the product to dwell for 2-4 minutes. Rinse the surface with warm water or a damp cloth. Ensure that no residue is left on the underlying material.

Equipment care

All equipment should be cleaned with water after use.

Storage

Recommended storage is in a cool, dry place with temperature 5°C – 30°C.

Shelf life: 12 months in original sealed container.

Technical Support

For technical support, please do not hesitate to contact us.

Protectcoat International
Spinding 16
5431 SN CUIJK
The Netherlands

Postbus 36
5430 AA CUIJK
The Netherlands

T: +31 (0)85-06 55 797

W: www.protectcoatint.com

Follow us on Social Media.



Important:

The content of this documentation is based on our experience with the product. Protectcoat International guarantees the quality of this products but expressly disclaims all liability if the user does not follow the recommendations and conditions of use of the products, especially but not exclusively in the case of faulty application, application by untrained personnel, use of products not compatible with Protectcoat International products or adverse weather conditions. For more information, consult the Safety Data Sheet. Protectcoat International accepts no liability arising from printing errors, mistakes/typing errors.

For the latest information, visit our website.
www.protectcoatint.com

Last updated: 01/01/2022