

# Protectcoat SF

### Description

**Protectcoat SF** is a water-based product that can be used to make the surface dirt and water repellent.

#### Usage

Protectcoat SF can be applied on:

- Concrete
- Stone
- Facades
- Bricks
- Etcetera

#### Advantage

The advantages of **Protectcoat SF** are:

- Dirt and water repellent
- Vapor permeable
- UV resistant
- Lifespan 8 10 years
- Easy to maintain the surface

#### **Application Tools**

Apply **Protectcoat SF** with a roller or a low pressure sprayer.



#### Health and Safety

- Breathing Protection: No breathing protection is required under normal use conditions with suitable ventilation.
  Wearing a facemask is advisable.
- Hand protection: Chemical resistant gloves should be worn.
- Skin protection: Wear protective clothing over exposed areas of skin.
- Eye protection: Chemical goggles should be worn.
- Ingestion: Ingestion may cause nausea and vomiting. Do not induce vomiting. Consult a Doctor.

KEEP OUT OF THE REACH OF CHILDEREN!

#### Recommendation

Always carry out a test first to ensure the finished result is acceptable.

Air temperature between  $5^{\circ}$ C –  $30^{\circ}$ C. Substrate temperature  $5^{\circ}$ C –  $25^{\circ}$ C

## Coverage rate

1-3 m<sup>2</sup> / liter. In case of an absorbent surface.

4-6 m<sup>2</sup> / liter. In case of a non-absorbent surface





# Protectcoat SF

#### Application

#### **Preparation:**

The surface must be dry, dust-free and clean. Shake well before use. If necessary, cover the windows and all surfaces not to be treated.

### **Application:**

Apply **Protectcoat SF** with a roller or a low pressure sprayer. The product should be applied crosswise

After 7 days, an anti-graffiti coating can be applied (Protectcoat AG10 coating).

#### **Equipment care**

Clean tools with water immediately after use.

#### Storage

Recommended storage is in a cool, dry place with temperature  $5^{\circ}C - 30^{\circ}C$ .

Shelf life: 12 months in original sealed container.

#### **Technical Support**

For technical support, please do not hesitate to contact us. Protectcoat International Spinding 16 5431 SN CUIJK The Netherlands

## Postbus 36 5430 AA CUIJK The Netherlands

Т:	+31 (0)85-06 55 797
W:	www.protectcoatint.com

#### Follow us on Social Media.



#### Important:

The content of this documentation is based on our experience with the product. Protectcoat International guarantees the quality of this products but expressly disclaims all liability if the user does not follow the recommendations and conditions of use of the products, especially but not exclusively in the case of faulty application, application by untrained personnel, use of products not compatible with Protectcoat International products or adverse weather conditions. For more information, consult the Safety Data Sheet. Protectcoat International accepts no liability arising from printing errors, mistakes/typing errors.

For the latest information, visit our website.

#### www.protectcoatint.com

Latest update: 01/01/2022