

Protectcoat SF Pro

Description

Protectcoat SF Pro is a water-based coating that is suitable for porous surfaces such as facades, roofs, floors etc. The coating offers a high protection against water, oil, grease, urine, algae, moss, chewing gum and more. This coating offers a protection of approximately 10 years on vertical surfaces.

Usage

Protectcoat SF Pro can be applied to:

- Concrete
- Stone
- Facades
- Floors
- Etcetera.


Advantage

The Advantages of **Protectcoat SF Pro** are:

- Vapour permeable
- Repels human and animal urine
- Water repellent
- Prevents frost damage
- UV resistant
- VOC free

Application Tools

Apply **Protectcoat SF Pro** with a roller or a low pressure sprayer.



Health and Safety

- Breathing Protection: No breathing protection is required under normal use conditions with suitable ventilation. Wearing a facemask is advisable.
- Hand protection: Chemical resistant gloves should be worn.
- Skin protection: Wear protective clothing over exposed areas of skin.
- Eye protection: Chemical goggles should be worn.
- Ingestion: Ingestion may cause nausea and vomiting. Do not induce vomiting. Consult a Doctor.

KEEP OUT OF THE REACH OF CHILDREN!

Recommendation

Always carry out a test first to ensure the finished result is acceptable.

Air temperature between 5°C – 30°C.

Substrate temperature 5°C – 25°C

Coverage rate

1-3 m² / liter.

In case of an absorbent surface.

5-10 m² / liter.

In case of a non-absorbent surface.



Protectcoat SF Pro

Application

Preparation:

The surface must be dry, dust-free and clean. Shake the product well before use.

Application:

Apply the **Protectcoat SF Pro** with a roller or a low pressure sprayer. Make sure that you cover the entire surface.

Drying time:

Depending on the temperature, layer thickness and the environment, **Protectcoat SF Pro** is hardened after approximately 7 days.

Equipment care

All equipment should be cleaned with water after use.

Storage

Recommended storage is in a cool, dry place with temperature 5°C – 30°C.

Shelf life: 12 months in original sealed container.

Technical Support

For technical support, please do not hesitate to contact us.

Protectcoat International

Spinding 16

5431 SN CUIJK

The Netherlands

Postbus 36

5430 AA CUIJK

The Netherlands

T: +31 (0)85-06 55 797

W: www.protectcoatint.com

Follow us on Social Media.



Important:

The content of this documentation is based on our experience with the product. Protectcoat International guarantees the quality of this products but expressly disclaims all liability if the user does not follow the recommendations and conditions of use of the products, especially but not exclusively in the case of faulty application, application by untrained personnel, use of products not compatible with Protectcoat International products or adverse weather conditions. For more information, consult the Safety Data Sheet. Protectcoat International accepts no liability arising from printing errors, mistakes/typing errors.

For the latest information, visit our website.

www.protectcoatint.com

Last updated: 01/01/2022