

# Protectcoat Stone SR

## Description

**Protectcoat Stone SR** is an effective but mild product for cleaning corrugated iron, stones, concrete, bricks, facades etc.. The product removes urine stains, algae, atmospheric pollution, etc. **Protectcoat Stone SR** is biodegradable.

## Usage

**Protectcoat Stone SR** can be applied to:

- Concrete
- Stone
- Plasterwork
- Corrugated iron
- Brickwork
- Terracotta
- Slates
- Etcetera.

## Advantage

The advantages of **Protectcoat Stone SR** are:

- Effective cleaner
- Biodegradable
- Does not damage the surface
- Can be used on various surfaces

## Application Tools

Apply **Protectcoat Stone SR** with a low pressure sprayer.



## Health and Safety

- Breathing Protection: No breathing protection is required under normal use conditions with suitable ventilation. Wearing a facemask is advisable.
- Hand protection: Chemical resistant gloves should be worn.
- Skin protection: Wear protective clothing over exposed areas of skin.
- Eye protection: Chemical goggles should be worn.
- Ingestion: Ingestion may cause nausea and vomiting. Do not induce vomiting. Consult a Doctor.

KEEP OUT OF THE REACH OF CHILDREN!

## Recommendation

Always carry out a test first to ensure the finished result is acceptable.

Air temperature between 5°C – 30°C.

Substrate temperature 5°C – 25°C

## Coverage rate

0,5m<sup>2</sup> / liter.

Depending on the degree of dirt.



# Protectcoat Stone SR

## Application

Apply **Protectcoat Stone SR** generously with a low pressure sprayer. Make sure that sprayer is opened properly. Let the product dwell for 5-30 minutes (depending on the dirtiness and the outside temperature). Use a brush to remove stubborn dirt. Note: do not use steel bristles. Rinse the entire surface with warm water under appropriate pressure. In case of extreme dirtiness, repeat the above steps.

## Equipment care

All equipment should be cleaned with water after use.

## Storage

Recommended storage is in a cool, dry place with temperature 5°C – 30°C.

Shelf life: 12 months in original sealed container.

## Technical Support

For technical support, please do not hesitate to contact us.

**Protectcoat International**  
**Spinding 16**  
**5431 SN CUIJK**  
**The Netherlands**

**Postbus 36**  
**5430 AA CUIJK**  
**The Netherlands**

**T:** +31 (0)85-06 55 797

**W:** [www.protectcoatint.com](http://www.protectcoatint.com)

**Follow us on Social Media.**



## Important:

The content of this documentation is based on our experience with the product. Protectcoat International guarantees the quality of this products but expressly disclaims all liability if the user does not follow the recommendations and conditions of use of the products, especially but not exclusively in the case of faulty application, application by untrained personnel, use of products not compatible with Protectcoat International products or adverse weather conditions. For more information, consult the Safety Data Sheet. Protectcoat International accepts no liability arising from printing errors, mistakes/typing errors.

For the latest information, visit our website.  
[www.protectcoatint.com](http://www.protectcoatint.com)

Latest update: 01/01/2022