

Protectcoat Wood SR

Description

Protectcoat Wood SR is a water-based product. It contains biodegradable organic acids. These natural acids are found in plants. This product will turn wood back to the original colour. **Protectcoat Wood SR** can also remove stains from tannin runs, rust, watermarks, iron, light dirt and stains caused by surface mould.

Usage

Protectcoat Wood SR can be used on a wide range of hardwoods and softwoods:

- Fences
- Sheds
- Decking
- Outdoor wooden furniture

Advantage

- Water-based product
- Biodegradable
- Can be used on a wide range of wood

Application Tools

Apply with a roller and non-metal brush.



Health and Safety

- Breathing Protection: No breathing protection is required under normal use conditions with suitable ventilation. Wearing a facemask is advisable.
- Hand protection: Chemical resistant gloves should be worn.
- Skin protection: Wear protective clothing over exposed areas of skin.
- Eye protection: Chemical goggles should be worn.
- Ingestion: Ingestion may cause nausea and vomiting. Do not induce vomiting. Consult a Doctor.

KEEP OUT OF THE REACH OF CHILDREN!

Recommendation

Always carry out a test first to ensure the finished result is acceptable. Avoid applying during heavy rain or very hot weather. Keep the product out of direct sunlight.

Attention:

Air temperature between 5°C – 30°C.

Substrate temperature 7°C – 25°C

Coverage rate

4-6 m² / liter.

Depending on wood type and porosity.



Protectcoat Wood SR

Application

Preparation:

Shake the product before use and ensure the wood is free from dirt and any remaining wood treatments before application.

Application:

First, using a brush or roller, apply **Protectcoat Wood SR** generously in the direction of the wood grain. For large areas, treat approximately 2m² at a time to prevent the product drying out. The wood to be treated should be coated evenly on all visible sides of each panel to prevent difference in colour.

Leave the **Protectcoat Wood SR** for 15 – 30 minutes. If it appears to be drying out, spray lightly with water. On dirty wood use a non-metal brush for scrubbing.

Rinse away the **Protectcoat Wood SR** thoroughly with clean water. It is not recommended to use a pressure washer as this clean.

Allow wood to dry fully for approximately 24 – 48 hours fully before treating with a protective finish.

Attention:

Keep this product away from metal and calcareous stone such as limestone and marble. If contact, wipe away immediately and rinse with water.

Equipment care

All equipment should be cleaned with water after use.

Storage

Recommended storage is in a cool, dry place with temperature 5°C – 30°C.

Shelf life: 12 months in original sealed container.

Technical Support

For technical support, please do not hesitate to contact us.

Protectcoat International

Spinding 16

5431 SN CUIJK

The Netherlands

Postbus 36

5430 AA CUIJK

The Netherlands

T: +31 (0)85-06 55 797

W: www.protectcoatint.com

Follow us on Social Media.



Important:

The content of this documentation is based on our experience with the product. Protectcoat International guarantees the quality of this products but expressly disclaims all liability if the user does not follow the recommendations and conditions of use of the products, especially but not exclusively in the case of faulty application, application by untrained personnel, use of products not compatible with Protectcoat International products or adverse weather conditions. For more information, consult the Safety Data Sheet. Protectcoat International accepts no liability arising from printing errors, mistakes/typing errors.

For the latest information, visit our website.

www.protectcoatint.com

Last updated: 01/07/2021