

# Train Wash Oxal

## Description

**Train Wash Oxal** is a cleaning product that easily removes brake dust and dirt (iron oxide) from locomotives, metros, trams, trains, etc. This product is water based, is an environmentally friendly product and has the Nordic Swan Ecolabel.

## Usage

**Train Wash Oxal** can be applied to:

- Locomotives
- Trains
- Trams
- Metros
- et cetera.

## Advantage

Advantages of the **Train Wash Oxal**:

- Eco-certified with it Nordic Swan Ecolabel
- Removes dirt easily
- Economical in use
- Does not affect the aluminum

## Application Tools

Can be used for automatic train washing plants.

## Manually:

Apply **Train Wash Oxal** with a brush:



## Health and Safety

- Breathing Protection: No breathing protection is required under normal use conditions with suitable ventilation. Wearing a facemask is advisable.
- Hand protection: Chemical resistant gloves should be worn.
- Skin protection: Wear protective clothing over exposed areas of skin.
- Eye protection: Chemical goggles should be worn.
- Ingestion: Ingestion may cause nausea and vomiting. Do not induce vomiting. Consult a Doctor.

KEEP OUT OF THE REACH OF CHILDREN!

## Recommendation

Always carry out a test first to ensure the finished result is acceptable.

Ideal processing temperature is 5 °C – 30 °C.

The ideal processing temperature for the substrate is 5°C – 25°C.

Do not let the product dry in the sun.

## Coverage rate

1 – 5m<sup>2</sup> / liter.

Depending on the degree of dirt.

## Dilute

### Train washing plants:

The ratio varies depending on the type of train washing plant, dirt and length of the program, from 5% to 20%.

### Manually:

From 10%.

Depending on the degree of dirt.



# Train Wash Oxal

## Application

**Machine:** This product can be used for automatic train washing plants.

## Manually:

Apply the product with a brush. Let the product act for 5 minutes. Rinse the surface with water. Do not allow the product to dry.

## Equipment care

All equipment should be cleaned with water after use.

## Storage

Recommended storage is in a cool, dry place with temperature 5°C – 25°C.  
Store frost free

Shelf life: 12 months in original sealed container.

## Technical Support

For technical support, please do not hesitate to contact us.

**Protectcoat International**  
**Spinding 16**  
**5431 SN CUIJK**  
**The Netherlands**

**Postbus 36**  
**5430 AA CUIJK**  
**The Netherlands**

**T:** +31 (0)85-06 55 797  
**W:** [www.protectcoatint.com](http://www.protectcoatint.com)

## Follow us on Social Media.



## Important:

The content of this documentation is based on our experience with the product. Protectcoat International guarantees the quality of this products but expressly disclaims all liability if the user does not follow the recommendations and conditions of use of the products, especially but not exclusively in the case of faulty application, application by untrained personnel, use of products not compatible with Protectcoat International products or adverse weather conditions. For more information, consult the Safety Data Sheet. Protectcoat International accepts no liability arising from printing errors, mistakes/typing errors.

For the latest information, visit our website.  
[www.protectcoatint.com](http://www.protectcoatint.com)

Last updated: 01/07/2022

